

## Specifications

General		
Frequency Range	VHF:136-174MHz	UHF:400-470MHz/350-390
Channel Capacity	16	
Channel Spacing	25KHz/12.5KHz	
Operating Temperature	-20°C~+60°C	
Antenna Impedance	50 Ω	
Operating Voltage	DC 3.7V(±20%)	
Battery Capacity	2200mAh(Li-ion)	
Frequency Stability	≤ ±2.5ppm	
Dimensions	59(L)*41(W)*103(H) mm	
Weight	220g(including battery pack)	
Transmitter		
Power Output	≤3W	
Modulation	16K ΦF3E(Wide)/8K50F3E(Narrow)	
Rated Audio Distortion	≤5%	
Adjacent Power	≥65 dB(Wide)/55 dB(Narrow)	
Modulation Limitation	≤5KHz(Wide)/2.5KHz(Narrow)	
Receiver		
Sensitivity	≤0.165 μ V(Wide)/ 0.2 μ V (Narrow)	
Adjacent Selectivity	≥60dB(Wide)/ 50dB (Narrow)	
Intermodulation Rejection Ratio	≥60dB(Wide)/ 50dB (Narrow)	
Spurious Suppression	≥60dB(Wide)/ 50dB (Narrow)	
Rated Audio Output Power	0.5W	
Rated Audio Distortion	≤5%	

## Accessories

### • Standard Accessories



Whip Antenna



Battery



Charger



Belt Clip



Hand Strap

### • Optional Accessories



Earpiece



Programming Cable



Remote Speaker



Stubby Antenna

**BelFone**  
Communications for Efficiency and Safety

**Fujian BelFone Communications Technology Co., Ltd.**

Add: A15, Huaqiao Economic Development Zone, Shuangyang,  
Luojiang, Quanzhou, Fujian, China 36200

Tel: +86 595 28396717

Fax: +86 595 22771635

Email: overseas@belfone.com

Website: www.belfone.com



To order in your local place, please contact:



## BF-350

Analog Portable

BF-350 is a light and robust two-way radio with excellent performance and stability. The paired whip antenna helps to extend talk range while its rich feature set meets all the conventional communication needs. BF-350 is a cost-effective analog solution for amateur users and small businesses like shops, restaurants, supermarkets, etc.

### Main Features

- Channel Prompt
- Time-out Timer (TOT)
- CTCSS/CDCSS/STE
- Squelch Levels (0-9)
- Busy Channel Lockout (BCL)
- Wide/Narrow Bands Ready



www.belfone.com

**BelFone**