

## Specifications

General	
Frequency Range	VHF:136-150, 150-174MHz UHF:340-370, 370-400, 400-430, 420-450, 440-470, 490-520
Channel Capacity	99
Channel Spacing	25KHz/12.5KHz
Antenna Impedance	50Ω
Voltage	13.8V DC cathode grounded
Current	≤11A
Operating Temperature	-30°C~+60°C
Dimensions/Weight	483(L)*88(W)*340(H) mm/ 9.7kg
Transmitter	
Power Output	50W
Frequency Stability	≤ ± 2.5 ppm
Modulation Mode	16K φ F3E(Wide) 8K φ F3E(Narrow)
Max Frequency Deviation	≤5KHz(Wide)/2.5KHz(Narrow)
Audio Distortion	≤3%
Audio Response	+1/-3dB
Adjacent Channel Selectivity	70dB at 25KHz, 60db at 12.5KHz
Spurious RF components	-36dBm(<1GHz) -30dBm(>1GHz)
Receiver	
Sensitivity (at 12dB SINAD)	Better than 0.25μV(Wide) Better than 0.28μV(Narrow)
Frequency Stability	≤ ± 2.5 ppm
Co-channel Suppression	≥ -7 dB
Adjacent Channel Selectivity	≥ 70 dB
Intermodulation Rejection	≥ 65dB
Spurious Response Rejection	≥ 65 dB
Block	≥ 90 dB
Audio Output Power	1W (8Ω)
Audio Response	+1/-3dB
Audio Distortion @ Rated Audio	≤3%
Bandwidth	20M
Environmental Specifications	
Operating Temperature	-20°C~ +60°C
Storage Temperature	-30°C~ +85°C
Dust& Water Proof	IP67
Humidity&Shock & Vibration	Per MIL-STD-810 C/D/E/F Standard

## Accessories

### • Standard Accessories



Fuse



Power Supply Cord

### • Optional Accessories



Programming Cable



Remote Speaker



**Fujian Belfone Communications Technology Co., Ltd.**

Add: A15, Huaqiao Economic Development Zone, Shuangyang,  
Luojiang, Quanzhou, Fujian, China 36200

Tel: +86 595 28396717

Fax: +86 595 22771635

Email: overseas@belfone.com

Website: www.belfone.com



To order in your local place, please contact:



## BF-5000

### Analog Repeater

Our versatile BF-5000 meets a variety of communication needs. Besides the conventional repeater mode, BF-5000 can also work as a base station and support such dispatching features as remote kill/stun/revive. The built-in CTCSS/CDCSS helps to filter out unwanted signals and increase repeating efficiency.



### Main Features

- Kill/Stun/Revive
- High Repeating Power
- PC Programming
- Time-out-timer(TOT)
- CTCSS/CDCSS
- Base Station /Repeater Dual Modes



www.belfone.com

