


Specifications

| General | |
|---------------------------------|--|
| Frequency Range | VHF: 87-108MHz(receive only)/136-174MHz UHF:350-390MHz(receive only)/400-470MHz |
| Channel Capacity | 199 |
| Channel Spacing | 25KHz/12.5KHz |
| Antenna Impedance | 50 Ω |
| Operating Voltage | DC 7.5V(±20%) |
| Battery Capacity | 1800mAh |
| Frequency Stability | ≤ ±2.5ppm |
| Dimensions | 61(L)*36(W)*117(H) mm |
| Weight | 217g (including battery pack) |
| Transmitter | |
| Power Output | H:5W; M:3W; L:1W |
| Modulation | 16K φ F3E(Wide)/8K φ F3E(Narrow) |
| Rated Audio Distortion | ≤5% |
| Adjacent Power | ≤60 dB(Wide)/55dB(Narrow) |
| Modulation Limitation | ≤ ±5KHz (Wide)/ ±2.5KHz(Narrow) |
| Receiver | |
| Sensitivity | Better than 0.2μV(width) Better than 0.25μV(narrow) |
| Adjacent Selectivity | ≥60dB(Wide)/ 50dB (Narrow) |
| Intermodulation Rejection Ratio | ≥60dB(Wide)/ 50dB (Narrow) |
| Spurious Suppression | ≥85dB(Wide)/ 80dB (Narrow) |
| Rated Audio Output Power | 0.5W |
| Rated Audio Distortion | ≤5% |

Accessories

• Standard Accessories




• Optional Accessories



Fujian Belfone Communications Technology Co., Ltd.
 Add: A15,Huaqiao Economic Development Zone, Shuangyang,
 Luojiang, Quanzhou,Fujian,China 36200
 Tel: +86 595 28396717
 Fax: +86 595 22771635
 Email: overseas@belfone.com
 Website: www.belfone.com



To order in your local place, please contact:



BF-5111UV

Analog Portable

Certified IP54 BF-5111UV is a multi-functional PMR radio capable of providing quality voice communication in a fashionable outfit. Besides conventional features such as Reverse Frequency, Switchable Power, Local Alarm, BF-5111UV is capable of crossband operation. This is an ideal radio for outdoor users.

Main Features

- Channel Scan
- Squelch Levels (0-9)
- H/L Power Switchable
- Built-in Flashlight
- CTCSS/CDCSS/STE
- Wide/Narrow Bands Switchable



www.belfone.com

