Specifications

General	
Frequency Range	VHF: 87-108MHz(receive only)/136-174MHz UHF:350-390MHz(receive only)/400-470MHz
Channel Capacity	199
Channel Spacing	25KHz/12.5KHz
Antenna Impedance	50Ω
Operating Voltage	DC 7.5V(±20%)
Battery Capacity	1800mAh
Frequency Stablility	≤±2.5ppm
Dimensions	61(L)*36(W)*117(H) mm
Weight	217g (including battery pack)
Transmitter	
Power Output	H:5W; M:3W; L:1W
Modulation	16KφF3E(Wide)/8KφF3E(Narrow)
Rated Audio Distortion	≤5%
Adjacent Power	≤60 dB(Wide)/55dB(Narrow)
Modulation Limitation	≤±5KHz (Wide)/±2.5KHz(Narrow)
Receiver	
Sensitivity	Better than 0.2μV(width) Better than 0.25μV(narrow)
Adjacent Selectivity	≥60dB(Wide)/ 50dB (Narrow)
Intermodulation Rejection Ratio	≥60dB(Wide)/ 50dB (Narrow)
Spurious Suppression	≥85dB(Wide)/ 80dB (Narrow)
Rated Audio Output Power	0.5W
Rated Audio Distortion	≤5%

Accessories

• Standard Accessories

Antenna

Battery

Charger

Belt Clip

Hand Strap

• Optional Accessories

Earpiece

Programming Cable

Remote Speaker

Car Charger

Power Bank

BelFone
Communications for Effciency and Safety

Fujian BelFone Communications Technology Co., Ltd.
Add: A15,Huaqiao Economic Development Zone, Shuangyang, Luojiang, Quanzhou,Fujian,China 36200
Tel: +86 595 28396717
Fax: +86 595 22771635
Email: overseas@belfone.com
Website: www.belfone.com

To order in your local place, please contact:

BF-5111UV

Analog Portable

Certified IP54 BF-5111UV is a multi-functional PMR radio capable of providing quality voice communication in a fashionable outfit. Besides conventional features such as Reverse Frequency, Switchable Power, Local Alarm, BF-5111UV is capable of crossband operation. This is an ideal radio for outdoor users.

Main Features

- Channel Scan
- H/L Power Switchable
- CTCSS/CDCSS/STE
- Squelch Levels (0-9)
- Built-in Flashlight
- Wide/Narrow Bands Switchable

www.belfone.com

BelFone