

## Specifications

General	
Frequency Range	UHF: 350-390MHz/400-470MHz
Channel Capacity	16
Channel Spacing	25KHz(Wide)/12.5KHz(Narrow)
Operating Voltage	7.4V DC (±20%)
Battery Capacity	2200mAh(Li-ion)
Frequency Stability	±2.5ppm
Antenna Impedance	50Ω
Operating Temperature	-20°C to +60°C
Weight	242g(including battery pack)
Dimensions	60(L) × 36(W) × 123(H)mm
Transmitter	
Power Output	≤5W
Modulation	16K φ F3E(Wide) 8K φ F3E(Narrow)
Noise and Harmonic	≤-36dBm
FM Noise	≤-40 dB
Audio Distortion	0.05
Adjacent Channel Power	≥65 dB(Wide)/55 dB(Narrow)
Modulation Limitation	≤5KHz(Wide) /2.5KHz(Narrow)
Receiver	
Sensitivity	≤0.165uV(Wide)/ 0.2uV(Narrow)
Adjacent Channel Selectivity	≥60dB(Wide)/ 50dB(Narrow)
Intermodulation	≥60dB(Wide)/ 50dB(Narrow)
Spurious Suppression	≥60dB(Wide)/ 50dB(Narrow)
SNR	≥45dB(Wide)/ 40dB(Narrow)
Rated Audio Output Power	500 mW
Rated Audio Distortion	≤5%

## Accessories

### • Standard Accessories



Short Antenna



Belt Clip



Battery



Charger



Hand Strap

### • Optional Accessories



Programming Cable



Earpiece



Car Charger



Remote Speaker



Long Antenna



### Fujian Belfone Communications Technology Co., Ltd.

Add: A15, Huaqiao Economic Development Zone, Shuangyang,  
Luojiang, Quanzhou, Fujian, China 36200

Tel: +86 595 28396717

Fax: +86 595 22771635

Email: overseas@belfone.com

Website: www.belfone.com



To order in your local place, please contact:



## BF-5112

### Analog Portable

BF-5112 is a smart two-way radio with a compact and rough design to guarantee durability of performance. With a comprehensive set of analog features and a long-lasting battery life, our BF-5112 is built to satisfy all the conventional communication needs for small businesses and amateur users.

### Main Features

- VOX
- Monitor
- Channel Scan
- PC Programming
- Squelch Level (0-9)
- Voice Prompt
- Time-out-timer(TOT)
- Wide/narrow Band Switch
- CTCSS/CDCSS and STE
- Busy Channel Lockout(BCL)



www.belfone.com

