

Specifications

General	
Frequency Range	VHF: 136-174MHz ; UHF: 350-390/400-470MHz
Channel Capacity	16
Channel Spacing	25KHz/12.5KHz
Operating Temperature	-20°C~+60°C
Antenna Impedance	50 Ω
Operating Voltage	DC 7.4V(±20%)
Battery Capacity	2200mAh
Frequency Stability	≤ ±2.5ppm
Dimensions	60(L)*36(W)*109(H) mm
Weight	253g (including battery pack)
Transmitter	
Power Output	H:5W L:1W
Modulation	16K ΦF3E(Wide)/8K ΦF3E(Narrow)
Noise and Harmonic	≤ -36dBm
FM Noise	≤ -40 dB
Rated Audio Distortion	0.05
Adjacent Power	≥65 dB(Wide)/60 dB(Narrow)
Modulation Limitation	≤5KHz(Wide) /2.5KHz(Narrow)
Receiver	
Sensitivity	≤ 0.2μV(Wide) /0.25μV(Narrow)
Adjacent Selectivity	≥60 dB(Wide)/55 dB(Narrow)
Intermodulation Rejection Ratio	≥60 dB(Wide)/55 dB(Narrow)
Spurious Suppression	≥60 dB(Wide)/55 dB(Narrow)
SNR	≥45 dB(Wide)/40 dB(Narrow)
Rated Audio Output Power	0.5W
Rated Audio Distortion	0.05

Accessories

• Standard Accessories



Antenna



Battery



Charger



Belt Clip



Hand Strap

• Optional Accessories



Earpiece



Programming Cable



Remote Speaker

BelFone
Communications for Efficiency and Safety

Fujian BelFone Communications Technology Co., Ltd.

Add: A15, Huaqiao Economic Development Zone, Shuangyang,
Luojiang, Quanzhou, Fujian, China 36200

Tel: +86 595 28396717

Fax: +86 595 22771635

Email: overseas@belfone.com

Website: www.belfone.com



To order in your local place, please contact:



BF-530

Analog Portable

BF-530 is a professional FM two-way radios with switchable transmitting powers, selectable squelch levels, programmable bandwidth and other advanced analog features. It is designed to deliver more safety and efficiency into your work and life. Its application ranges across many fields of work, such as restaurants, warehouses, outdoor activities, etc.

Main Features

- H/L Power Switchable
- Busy Channel Lockout(BCL)
- PC Programming
- Programmable Bandwidth
- CTCSS/CDCSS
- Squelch Levels(0-9)



www.belfone.com

BelFone